A study of oxy-coal combustion with steam addition and biomass blending by thermogravimetric analysis

M.V. Gil, J. Riaza, L. Álvarez, C. Pevida, J.J. Pis, F. Rubiera *

Instituto Nacional del Carbón, CSIC, Apartado 73, 33080 Oviedo, Spain

Abstract

The thermal characteristics of pulverized coal have been studied under oxy-fuel combustion conditions using non-isothermal thermogravimetric analysis. The atmospheres used were 21%O₂/79%N₂, 21%O₂/79%CO₂, 30%O₂/70% O₂ and 35%O₂/65%CO₂. Coal blends of coal with 10 and 20% of biomass were also studied under these atmospheres. The addition of 10 and 20% of steam was evaluated for the oxy-fuel combustion atmospheres with 21 and 30% of O₂ in order to study the effect of the wet recirculation of flue gas. The results obtained were similar for all the different rank coals and indicated that replacing N₂ by CO₂ in the combustion atmosphere with 21% of O₂ caused a slight decrease in the rate of mass loss and delayed the burning process of the coal, biomass and coal/biomass blend samples. When the O₂ concentration was increased to 30 and 35% in the oxy-fuel combustion atmosphere, the rate of mass loss increased, the burning process occurred at lower temperatures and it was shorter in duration. An increase in the rate of mass loss and a reduction in burning time and temperature were observed after the addition of steam to the oxy-fuel combustion atmosphere. No relevant differences between the 10 and 20% steam concentrations were observed.

---

* Corresponding author. Tel.: +34 985 118 975; Fax: +34 985 297 662.

E-mail address: frubiera@incar.csic.es (F. Rubiera)

Keywords: Oxy-fuel combustion; Pulverized coal; Biomass; Steam; TG

1. Introduction

Interest in coal as an energy source for the future has recently been revived due to the stability of its supply and its relatively low cost. For these reasons, it is likely that coal will occupy an important position in the energy mix in the foreseeable future [1,2]. However, the emissions of greenhouse gas carbon dioxide from coal-fired power plants are very high and their effect on global climate change has been acknowledged worldwide. Various strategies for their reduction and sequestration are under study, including improvements in the efficiency of existing power plants, the introduction of advanced combined cycle power plants and the capture and storage of CO₂ [3].

Carbon capture and storage (CCS) is considered one of the most realistic options for reducing CO₂ emissions from fossil fuel use, particularly from large-scale stationary power plants. The main problem, however, is that the combustion of fossil fuel in air leads to a diluted concentration of CO₂ in the flue gas stream (typically 15% by volume), rendering it unsuitable for direct sequestration in a supercritical state by compression, a process which requires a high concentration of CO₂ [4,5].

As an alternative, oxy-fuel combustion is considered as a promising new approach for CO₂ capture. Oxy-fuel combustion technology involves the combustion of pulverized coal in a mixture of oxygen (as opposed to air) and recirculated flue gas (mainly CO₂ and H₂O). The advantages of this approach are that it offers a way of avoiding the excessively high flame temperatures characteristic of fuel combustion in oxygen, carries the heat through the boiler, reduces the net volume of flue gas and substantially

increases the concentration of carbon dioxide in the flue gas. A flue gas consisting mainly of CO₂ (80-95% by volume) and water vapour is then generated. The water vapour can be easily removed by condensation, making it easier to purify the remaining CO₂ [6].

The successful implementation of O₂/CO₂ technology in conventional pulverized coal boilers depends on a full understanding of the changes that result from replacing N₂ with CO₂ in the oxidizer stream [7]. Although many published works have focused on the oxy-fuel combustion process [8-12], the effect of adding steam to the oxy-fuel combustion atmosphere has hardly been studied [13].

Alternatively, biomass is a renewable fuel which can be used for reducing CO₂ emissions. This source of energy is considered carbon neutral because the carbon dioxide released during biomass utilization is recycled as an integral part of the carbon cycle. The combination of oxy-fuel combustion with biomass could be used as a sink for CO₂ and therefore more knowledge about cofiring coal and biomass under oxy-fuel conditions is needed [14].

Thermogravimetric analysis (TG) is one of the most common techniques used to rapidly investigate and compare thermal events during the combustion and pyrolysis of solid raw materials, such as coal, woods, etc. [15-22]. Although extrapolation to other devices at a larger scale cannot be performed directly, the information obtained from the combustion profiles in the TG could be used for an initial evaluation of the behaviour of the combustion on an industrial scale [23]. This would contribute to an understanding of coal combustion behaviour and prove very useful both from a fundamental viewpoint and for the comparison of samples [24].

In this work, thermogravimetric analysis (TG) was used in order to study the effect of replacing N_2 with CO_2 in a combustion atmosphere and of enhanced levels of O_2 in an oxy-fuel combustion atmosphere upon the thermal characteristics of different rank coals and coal/biomass blends. Oxy-fuel combustion with steam addition was also evaluated in order to study the effect of the wet recirculation of flue gas.

2. Materials and methods

2.1. Materials

Ten coals of different rank [25] were used in this work: an anthracite (AC), a semi-anthracite (HVN), two medium-volatile bituminous coals (UM and SAA) and six high-volatile bituminous coals (DAB, SAB, M6N, BA, CAB and NZ). A biomass, olive waste (OW), was also employed. The samples were ground and sieved to obtain a particle size fraction of 75-150 μm . The proximate analysis and the high heating value of the samples are presented in Table 1.

2.2. Apparatus and procedure

The techniques employed in this study were thermogravimetric analysis (TG) and derivative thermogravimetry (DTG). Non-isothermal TG was performed using a Setaram TAG24 analyser. Approximately 5 mg of sample was used for each experiment. A small amount of sample and a slow heating rate were used to avoid heat transfer limitations and to minimize mass transfer effects. The samples were heated at a heating rate of $15\text{ }^{\circ}C\text{ min}^{-1}$ in different atmospheres from room temperature to $1000\text{ }^{\circ}C$. The simulated air combustion atmosphere was 21% O_2 /79% N_2 . Three O_2/CO_2 oxy-fuel combustion conditions were used (21, 30 and 35% of O_2). The addition of 10 and 20%

of steam (as a replacement for CO₂) to an oxy-fuel combustion atmosphere containing 21 and 30% of O₂ was also evaluated in order to study the effect of the wet recirculation of flue gas. The total flow rate of all the mixtures of gases was 150 cm³ min⁻¹. The steam generator consisted of a CEM® (Controlled Evaporator and Mixer), in which water and O₂/CO₂ were mixed and heated up to 175 °C. Liquid and mass flow controllers were used to control the flow rates of the water, O₂, CO₂ and N₂. The derivative curves (DTG) of the samples were represented as a function of temperature.

2.3. Determination of the combustion parameters

From the combustion profiles, the following thermal parameters were calculated for characterizing the combustion process: initial temperature (T_i), final temperature (T_f), peak temperature (T_{peak}), temperature corresponding to a conversion degree of 50% (T_{50}), maximum rate of mass loss (DTG_{max}), average rate of mass loss (Average DTG) and coal reactivity index (R_C). The initial temperature (T_i) and the final temperature (T_f) were taken as the temperature values (after the initial loss of moisture) at which the rate of mass loss was 1% min⁻¹. The peak temperature (T_{peak}) corresponds to the temperature at which maximum rate of mass loss occurs [26]. The temperature value at the maximum rate of mass loss is usually considered inversely proportional to the reactivity and combustibility of the sample [27], whereas the maximum rate of mass loss is considered directly proportional to the reactivity of the sample [28]. The average rate of mass loss (Average DTG) is the ratio between the burnout fraction and time during the temperature range of initial to final temperature. The coal reactivity index (R_C) was used to evaluate the burning performance of pulverized coal, defined as:

$$R_C = 1/m_0 (dm/dt)_{max} \quad (1)$$

where $(dm/dt)_{\max}$ is the maximum combustion rate and m_0 is the initial mass of ash free sample. It should be noted that the greater the R_C value, the higher the combustion reactivity.

3. Results and discussion

3.1. Combustion characteristics of pulverized coal under air and O_2/CO_2 atmospheres

DTG curves for the AC, HVN, DAB and NZ coal samples under the different combustion and oxy-fuel combustion atmospheres are shown as example in Fig. 1. The DTG curves for the other coals (not represented) showed similar behaviour. From the combustion profiles (Fig. 1), it can be seen that coal combustion in the O_2/N_2 atmosphere differed from that in the O_2/CO_2 atmosphere at the same oxygen concentration (21%). For all the coals studied in the 21% O_2 /79% CO_2 atmosphere, the curves of mass loss rate shifted to higher temperatures in relation to those in the 21% O_2 /79% N_2 conditions. This implies that there was a delay in the burning process, which may have been due to the higher specific heat of CO_2 compared to N_2 , leading to comparatively lower gas temperatures and in turn to a reduction of the fuel particle temperatures during oxy-fuel combustion in comparison to combustion in air. Li et al. [6] found lower rates of mass loss and higher burning times for a bituminous coal after replacing N_2 with CO_2 from an air atmosphere, indicating that the devolatilization rate of coal was lower under a CO_2 atmosphere than under a N_2 atmosphere. These authors thus concluded that replacing N_2 with CO_2 was unfavourable to coal combustion.

On the other hand, if the oxygen concentration was increased under the oxy-fuel combustion atmospheres (30% O_2 /70% CO_2 and 35% O_2 /65% CO_2), the DTG curves moved to lower temperatures, and the rate of mass loss increased whereas the burning

time decreased in comparison to the values achieved in the 21%O₂/79%N₂ combustion atmosphere (Fig. 1). This may be because a higher oxygen concentration enhances the devolatilization and combustion of coal samples. Under a lower oxygen concentration, the ignition of both the volatile matter and char would be retarded [8].

Table 2 summarizes the combustion parameters for the AC, HVN, DAB and NZ coals, whose results are similar to those of the other coals studied. It can be seen that the initial temperature, T_i , for the coal samples was similar or slightly higher under oxy-fuel combustion atmosphere with 21% of O₂ compared to air. However, T_i decreased as the O₂ concentration increased in the O₂/CO₂ atmosphere. The same tendency is observed for the final temperature, T_f , the peak temperature, T_{peak} , and the temperature corresponding to a conversion degree of 50%, T_{50} . In contrast, the Average DTG and DTG_{max} values followed the opposite tendency. They were slightly lower under the air atmosphere than under the oxy-fuel atmosphere containing 21% of O₂, but they increased as the O₂ concentration increased in the O₂/CO₂ atmosphere. Table 2 also shows that, in general, the coal reactivity index (R_C) in the 21%O₂/79%CO₂ atmosphere was slightly lower than that in the 21%O₂/79%N₂ atmosphere, but was higher in the 30%O₂/70%CO₂ and 35%O₂/65%CO₂ atmospheres, these two atmospheres showing similar values of coal reactivity.

If the characteristic temperatures for all the different rank coals are compared, the order is the following: AC>HVN>UM=BA>SAB=SAA≥DAB> CAB≥M6N>NZ. This order approximately coincides with that of coal rank (Table 1).

3.2. Combustion characteristics of biomass and coal/biomass blends under air and O₂/CO₂ atmospheres

Fig. 2 shows the DTG curves for the biomass sample, OW, and the coal/biomass blends under the oxy-fuel combustion atmospheres. From the combustion profiles (Fig. 2), it can be seen that the combustion of the OW, 90%HVN+10%OW and 80%HVN+20%OW samples in the O₂/N₂ atmosphere differed from that of the O₂/CO₂ atmosphere at the same oxygen concentration (21%). As in the case of the coals, in the 21%O₂/79%CO₂ atmosphere, the curves of mass loss rate shifted to higher temperatures in relation to those in the 21%O₂/79%N₂ conditions, indicating that there was a delay in the combustion process. However, for the biomass and coal/biomass blend samples, when the oxygen concentration was increased under the oxy-fuel combustion atmospheres (30%O₂/70%CO₂ and 35%O₂/65%CO₂), the DTG curves moved to lower temperatures, the rate of mass loss increased and the burning time decreased with respect to the corresponding parameters in the 21%O₂/79%N₂ combustion atmosphere.

Fig. 2 also shows that an initial mass loss occurred between 25-105 °C for all the samples, due to moisture evaporation, after which two mass loss stages occurred in the OW and blend samples, compared to a one stage mass loss for the HVN sample (Fig.1). The second mass loss stage in the OW sample was possibly due to the release of volatiles and their combustion, while the final mass loss may have been due to char oxidation. In the case of the blends, the second mass loss was very small, due to the low proportion of biomass in the blend, the last peak closely resembling that of the coal sample, presumably because coal was the predominant component of the blend.

The combustion parameters for these samples are summarized in Table 3. In the case of the OW and blend samples, the parameters were calculated only taking into

consideration the last mass loss stage, so that they could be then compared with those of the HVN coal sample. For all the combustion and oxy-fuel combustion atmospheres, it can be observed that the highest values of T_i , T_f , T_{50} , DTG_{max} and Average DTG corresponded to the HVN samples, followed by those of the 90%HVN+10%OW and the 80%HVN+20%OW samples in that order. Small differences were found in the T_{peak} and R_C values of the samples. The addition of biomass to the coal caused a decrease in the combustion and oxy-fuel combustion temperatures. Biomass is a fuel with high reactivity and high volatile matter content (Table 1), which can lead to a faster reaction and to an improvement in the combustion behaviour of a coal in agreement with the results of other works [18,29,30].

3.3. Effects of steam addition upon the oxy-fuel combustion characteristics of pulverized coal

Fig. 3 compares the DTG curves for the AC, HVN, DAB and NZ coal samples under the 21%O₂/79%CO₂ and 30%O₂/70%CO₂ oxy-fuel combustion atmospheres with those corresponding to the same atmosphere after the replacement of CO₂ with 10 and 20% of steam. It can be observed that the addition of steam shifted the DTG curves to lower temperatures and generally caused an increase in the rate of mass loss and a decrease in combustion time with respect to those in the 21%O₂/79%CO₂ or 30%O₂/70%CO₂ oxy-fuel combustion atmospheres, probably due to the fact that the specific heat capacity of H₂O is lower than that of CO₂ [31], as a result of which the combustion stage was brought forward. However, no relevant differences were observed from the addition of 10 and 20% of steam (Fig. 3).

4. Conclusions

The different coals studied exhibited different combustion behaviours under O_2/CO_2 oxy-fuel conditions with respect to air combustion conditions. The coal, biomass and coal/biomass blend samples showed slightly higher reactivities under air compared to oxy-fuel conditions at the same O_2 level, since the replacement of O_2 by CO_2 caused the rate of mass loss to decrease and the burning process occurred at higher temperatures. However, once the O_2 concentration had been increased to 30 and 35% in the oxy-fuel combustion atmosphere, the rate of mass loss rose and the burning process was brought forward and shortened. The addition of biomass to coal caused a decrease in the combustion and oxy-fuel combustion temperatures. The replacement of 10 and 20% of CO_2 with steam in the oxy-fuel combustion atmosphere of the coal resulted in an increase in the rate of mass loss and a decrease in the burning time, no significant differences being observed between the two steam concentrations.

Acknowledgements

The present study was carried out with financial support from the Spanish MICINN (Project PS- 120000-2005-2) co-financed by the European Regional Development Fund. L.A. and J.R. acknowledge funding from the CSIC JAE program, which was co-financed by the European Social Fund, and the Asturias Regional Government (PCTI program), respectively.

References

- [1] BP. 2009. BP Statistical Review of World Energy June 2009. <http://www.bp.com> (Last accessed: November 22th, 2010).

- [2] Buhre BJP, Elliott LK, Sheng CD, Gupta RP, Wall TF. Oxy-fuel combustion technology for coal-fired power generation. *Prog Energy Combust Sci* 2005;31:283-307.
- [3] Bejarano PA, Levendis YA. Single-coal-particle combustion in O_2/N_2 and O_2/CO_2 environments. *Combust Flame* 2008;153:270-87.
- [4] Rathnam RK, Elliott LK, Wall TF, Liu Y, Moghtaderi B. Differences in reactivity of pulverised coal in air (O_2/N_2) and oxy-fuel (O_2/CO_2) conditions. *Fuel Process Technol* 2009;90:797-802.
- [5] Toftegaard MB, Brix J, Jensen PA, Glarbor P, Jensen AD. Oxy-fuel combustion of solid fuels. *Prog Energy Combust Sci* 2010;36:581-625.
- [6] Li Q, Zhao C, Chen X, Wu W, Li Y. Comparison of pulverized coal combustion in air and in O_2/CO_2 mixtures by thermo-gravimetric analysis. *J Anal Appl Pyrolysis* 2009;85:521-8.
- [7] Molina A, Shaddix CR. Ignition and devolatilization of pulverized bituminous coal particles during oxygen/carbon dioxide coal combustion. *Proc Combust Inst* 2007;31:1905-12.
- [8] Huang X, Jiang X, Han X, Wang H. Combustion characteristics of fine- and micro-pulverized coal in the mixture of O_2/CO_2 . *Energy Fuels* 2008;22:3756-62.
- [9] Li X, Rathnam RK, Yu J, Wang Q, Wall T, Meesri C. Pyrolysis and combustion characteristics of an Indonesian Low-Rank Coal under O_2/N_2 and O_2/CO_2 conditions. *Energy Fuels* 2010;24:160-4.
- [10] Liu H, Zailani R, Gibbs BM. Comparisons of pulverized coal combustion in air and in mixtures of O_2/CO_2 . *Fuel* 2005;84:833-40.
- [11] Várhegyi G, Szabó P, Jakab E, Till F. Mathematical modeling of char reactivity in $Ar-O_2$ and CO_2-O_2 mixtures. *Energy Fuels* 1996;10:1208-14.
- [12] Zhang L, Binner E, Qiao Y, Li C-Z. In situ diagnostics of Victorian brown coal combustion in O_2/N_2 and O_2/CO_2 mixtures in drop-tube furnace. *Fuel* 2010;89:2703-12.
- [13] Nozaki T, Takano S, Kiga T, Omata K, Kimura N. Analysis of the flame formed during oxidation of pulverized coal by an O_2-CO_2 mixture. *Energy* 1997;22:199-205.
- [14] Arias B, Pevida C, Rubiera F, Pis JJ. Effect of biomass blending on coal ignition and burnout during oxy-fuel combustion. *Fuel* 2008;87:2753-9.
- [15] Pis JJ, de la Puente G, Fuente E, Morán A, Rubiera F. A study of the self-heating of fresh and oxidized coals by differential thermal analysis. *Thermochim Acta* 1996;279:93-101.
- [16] Rubiera F, Morán A, Martínez O, Fuente E, Pis JJ. Influence of biological desulphurisation on coal combustion performance. *Fuel Process Technol* 1997;52:165-73.
- [17] Niu SL, Lu CM, Han KH, Zhao JL. Thermogravimetric analysis of combustion characteristics and kinetic parameters of pulverized coals in oxy-fuel atmosphere. *J Therm Anal Calorim* 2009;98:267-274.
- [18] Arenillas A, Rubiera F, Pis JJ, Jones JM, Williams A. The effect of the textural properties of bituminous coal chars on NO emissions. *Fuel* 1999;78:1779-85.
- [19] Jiang XM, Cui ZG, Han XX, Yu HL. Thermogravimetric investigation on combustion characteristics of oil shale and high sulphur coal mixture. *J Therm Anal Calorim* 2006;85:761-4.

- [20] Buryan P, Staff M. Pyrolysis of the waste biomass. *J Therm Anal Calorim* 2008;93:637-40.
- [21] Mothé CG, de Miranda IC. Characterization of sugarcane and coconut fibers by thermal analysis and FTIR. *J Therm Anal Calorim* 2009;97:661-5.
- [22] Slovák V, Taraba B. Effect of experimental conditions on parameters derived from TG-DSC measurements of low-temperature oxidation of coal. *J Therm Anal Calorim* 2010;101:641-6.
- [23] Cumming JW, McLaughlin J. The thermogravimetric behaviour of coal. *Thermochim Acta* 1982;57:253-72.
- [24] Rubiera F, Arenillas A, Arias B, Pis JJ. Modification of combustion behaviour and NO emissions by coal blending. *Fuel Process Technol* 2002;77:111-7.
- [25] ASTM Standard D 388. Standard Classification of Coals by Rank. 2005.
- [26] Rubiera F, Arenillas A, Fuente E, Miles N, Pis JJ. Effect of the grinding behaviour of coal blends on coal utilisation for combustion. *Powder Technol* 1999;105:351-6.
- [27] Haykırı-Açma H. Combustion characteristics of different biomass materials. *Energ Convers Manage* 2003;44:155-62.
- [28] Zheng JA, Koziński JA. Thermal events occurring during the combustion of biomass residue. *Fuel* 2000;79:181-92.
- [29] Gil MV, Casal D, Pevida C, Pis JJ, Rubiera F. Thermal behaviour and kinetics of coal/biomass blends during co-combustion. *Bioresource Technol* 2010;101:5601-8.
- [30] Kastanaki E, Vamvuka D. A comparative reactivity and kinetic study on the combustion of coal-biomass char blends. *Fuel* 2006;85:1186-93.
- [31] Khare SP, Wall TF, Farida AZ, Liu Y, Moghtaderi B, Gupta RP. Factors influencing the ignition of flames from air-fired swirl pf burners retrofitted to oxy-fuel. *Fuel* 2008;87:1042-9.

Figure captions

Fig. 1. DTG curves for coal combustion under different atmospheres

Fig. 2. DTG curves for the combustion of biomass and coal/biomass blends under different atmospheres

Fig. 3. DTG curves for coal combustion under oxy-fuel atmospheres with 21 and 30% of O₂ containing steam

Table 1. Proximate analysis and high heating value of the coals

Sample	AC	HVN	UM	SAA	DAB	SAB	M6N	BA	CAB	NZ	OW
Origin	Spain	Spain	Mexico	South Africa	China	South Africa	Mexico	Spain	Colombia	New Zealand	Spain
Rank	an	sa	mvb	mvb	hvb	hvb	hvb	hvb	hvb	hvb	---
Proximate Analysis ^a											
Moisture content/wt. %	2.3	1.1	0.4	2.6	2.9	2.4	1.8	1.2	4.3	11.5	9.2
Ash/wt. %, db	14.2	10.7	21.1	14.9	10.9	15.0	30.2	6.9	4.4	2.9	7.6
V.M./wt. %, db	3.6	9.2	23.7	25.6	28.8	29.9	30.6	33.9	39.6	47.9	71.9
F.C./wt. %, db ^b	82.2	80.1	55.2	59.5	60.3	55.1	39.2	59.2	56.0	49.2	20.5
High heating value/kJ kg ⁻¹ , db	29160	31818	27826	27952	28825	27780	23057	33081	30965	27943	19905

an: anthracite; sa: semi-anthracite; mvb: medium-volatile bituminous coal; hvb: high-volatile bituminous coal.

db: dry basis.

^a The proximate analysis was conducted in a LECO TGA-601.

^b Calculated by difference.

Table 2. Combustion parameters of the coals under different atmospheres

Sample	Atmosphere	$T_i/^{\circ}\text{C}$	$T_f/^{\circ}\text{C}$	$T_{\text{peak}}/^{\circ}\text{C}$	$T_{50}/^{\circ}\text{C}$	$\text{DTG}_{\text{max}}/\% \text{ s}^{-1}$	Average $\text{DTG}/\% \text{ s}^{-1}$	$R_c/\% \text{ kg}^{-1} \text{ s}^{-1}$
AC	21%O ₂ /79%N ₂	560	732	625	634	0.261	0.141	53996
	21%O ₂ /79%CO ₂	561	734	633	636	0.248	0.139	50849
	30%O ₂ /70%CO ₂	545	707	608	613	0.303	0.146	65117
	35%O ₂ /65%CO ₂	540	696	600	603	0.333	0.154	71177
HVN	21%O ₂ /79%N ₂	482	644	567	566	0.301	0.149	60252
	21%O ₂ /79%CO ₂	484	650	570	569	0.287	0.147	55352
	30%O ₂ /70%CO ₂	470	627	547	547	0.358	0.157	78894
	35%O ₂ /65%CO ₂	465	616	540	539	0.392	0.163	77706
DAB	21%O ₂ /79%N ₂	357	588	516	499	0.229	0.105	48817
	21%O ₂ /79%CO ₂	360	593	520	503	0.222	0.103	45983
	30%O ₂ /70%CO ₂	351	576	501	490	0.255	0.109	55768
	35%O ₂ /65%CO ₂	346	567	495	483	0.265	0.111	56410
NZ	21%O ₂ /79%N ₂	293	504	410	405	0.267	0.104	49585
	21%O ₂ /79%CO ₂	294	506	411	405	0.260	0.103	49821
	30%O ₂ /70%CO ₂	288	497	406	400	0.293	0.105	57537
	35%O ₂ /65%CO ₂	283	486	395	393	0.399	0.107	73462

T_i : initial temperature; T_f : final temperature; T_{peak} : peak temperature; T_{50} : temperature corresponding to a conversion degree of 50%; DTG_{max} : maximum rate of mass loss; Average DTG: average rate of mass loss; R_c : coal reactivity index.

Table 3. Combustion parameters of the biomass and the coal/biomass blends under different atmospheres

Atmosphere	Sample	$T_i/^{\circ}\text{C}$	$T_f/^{\circ}\text{C}$	$T_{\text{peak}}/^{\circ}\text{C}$	$T_{50}/^{\circ}\text{C}$	$\text{DTG}_{\text{max}}/\% \text{ s}^{-1}$	Average DTG/ $\% \text{ s}^{-1}$	$R_c/\% \text{ kg}^{-1} \text{ s}^{-1}$
21%O ₂ /79%N ₂	HVN	482	644	567	566	0.301	0.149	60252
	90%HVN-10%OW	465	641	565	561	0.282	0.132	62291
	80%HVN-20%OW	455	623	559	546	0.278	0.129	58044
	OW	367	520	475	302	0.118	0.064	24636
21%O ₂ /79%CO ₂	HVN	484	650	570	569	0.287	0.147	55352
	90%HVN-10%OW	469	645	570	564	0.264	0.130	54590
	80%HVN-20%OW	460	628	565	552	0.269	0.127	55948
	OW	370	522	475	305	0.118	0.064	23807
30%O ₂ /70%CO ₂	HVN	470	627	547	547	0.358	0.157	78894
	90%HVN-10%OW	453	619	545	542	0.337	0.142	69394
	80%HVN-20%OW	452	608	545	535	0.308	0.131	61221
	OW	371	514	467	308	0.122	0.067	31640
35%O ₂ /65%CO ₂	HVN	465	616	540	539	0.392	0.163	77706
	90%HVN-10%OW	453	611	540	536	0.358	0.145	76386
	80%HVN-20%OW	448	601	535	529	0.335	0.137	65442
	OW	365	509	461	302	0.129	0.067	25639

T_i : initial temperature; T_f : final temperature; T_{peak} : peak temperature; T_{50} : temperature corresponding to a conversion degree of 50%; DTG_{max} : maximum rate of mass loss; Average DTG: average rate of mass loss; R_c : coal reactivity index.

Fig. 1. DTG curves for coal combustion under different atmospheres

Fig. 2. DTG curves for the combustion of biomass and coal/biomass blends under different atmospheres

Fig. 3. DTG curves for coal combustion under oxy-fuel atmospheres with 21 and 30% of O₂ containing steam