Analysis of Rigid Body Interactions for Compliant Motion Tasks Using the Grassmann-Cayley Algebra

E. Staffetti F. Thomas

Institut de Robòtica i Informàtica Industrial (UPC-CSIC)

Gran Capità 2-4, 08034 Barcelona, Spain

{estaffetti, fthomas}@iri.upc.es

Abstract

This paper studies the statics and the instantaneous kinematics of a rigid body constrained to keep an arbitrary number of surface-surface contacts with a rigid static environment during its motion.

These properties are analyzed under the frictionless assumption by modelling each contact with a kinematic chain that instantaneously gives the same motion freedom as the contact itself and by studying the resulting parallel chain using the Grassmann-Cayley Algebra.

With this algebra twists and wrenches can be expressed by means of extensors and operated using the join and meet operators. Moreover, the duality inherent in this algebra is used to reflect the reciprocity condition between possible twists and admissible wrenches between partially constrained rigid bodies.

1 Introduction

Compliant motion tasks are manipulation tasks that involve contacts between the manipulated object, say M , and the static environment, say S , in which the trajectory of the manipulator is modified depending on the contact forces arising between them.

In these applications it is important to know how S constrains the motion of M and the possible reaction forces that might arise in their interaction in order to appropriately choose the generalized motions and forces to accomplish a given task.

In this paper we shall study the *kinestatics* of a partially constrained rigid body, that is, the statics and instantaneous kinematics of a rigid object constrained to keep an arbitrary number of surface-surface contacts with a rigid static environment, thus extending the work presented in [1] in which some aspects of the same problem were studied using the Grassmann-Cayley

Algebra on polyhedral approximations of the objects involved in the motion.

The precision in the execution of a compliant task relies on the accuracy of the model but exact modelling of the motion constraints could be impractical. So, with the hypothesis of the absence of friction, we use a second order local approximation that takes into account not only the tangent plane at the contact point but also the principal directions and the principal curvatures of the surface patches at that point, which are easily computable from both parametric and implicit representations of surfaces [2, 3].

If each contact between M and S is translated into a kinematic chain that instantaneously gives the same motion freedom, a parallel mechanism is obtained whose instantaneous mobility coincides with that of M with reference to S . This model has been introduced in [4] where the kinematic chains that represent the surface-surface contacts are called *virtual contact manipulators* and the effects of multiple contacts are studied by means of their Jacobian matrices.

The parallel mechanism resulting from translating each contact into its instantaneously equivalent kinematic chain is herein described and analyzed using the Grassmann-Cayley Algebra focusing the attention on the relationship between possible twists and admissible wrenches of the body that represents the moving object. In this way the results on the kinestatics of serial and parallel manipulators [5] can be applied to the analysis of rigid body interaction.

A comprehensive reference on the abstract properties of the Grassmann-Cayley Algebra can be found in [6] while [7, 8, 9] emphasize the concrete approach to this algebra and give more detail on the connections to Robotics. This algebra is briefly reviewed in Sect. 2.

Any instantaneous motion of a rigid body can be described as a twist on a screw and any set of forces and moments that act on a rigid body can be described as a wrench on a screw [10, 11]. Sect. 3 describes

how instantaneous screws can be represented by means of the concept of extensor of the Grassmann-Cayley Algebra.

Moreover, the twist and wrench spaces resulting from serial or parallel connections of motion constraints can be computed by means of the join and meet operators of this algebra and its inherent duality can be used to reflect the reciprocity between twists and wrenches of partially constrained rigid bodies. This is discussed in Sect. 4.

Sect. 5 presents the adopted equivalent kinematic model of a point surface-surface contact and in Sect. 6 the kinestatic analysis of the interaction between two rigid bodies is reported.

An example in which these concepts are applied to the study of the possible twists and admissible wrenches for a moving body that makes three point contacts with a static environment is presented in Sect. 7. Finally, Sect. 8 contains the conclusions.

2 The Grassmann-Cayley Algebra

In this section we report the most relevant properties of a version of the Grassmann-Cayley Algebra that involves Plücker coordinates. Further details can be found in [8].

It is convenient to start from some basic concept about projective space and homogeneous coordinates. If $\mathbf{x} = (x_1, x_2, \dots, x_m)^t$ is a point in $\mathbb{R}^m$ given in terms of *Cartesian coordinates*, the vector $x = (x_1, x_2, \dots, x_m, 1)^t$ is defined to be its *homogeneous coordinate vector*.

If we allow points with the last coordinate 0 for representing *projective points* at infinity, the standard m -dimensional *projective space* that includes $\mathbb{R}^m$ is obtained. So, we represent $\mathbb{R}^m$ with points at infinity by a $(m+1)$ -dimensional vector space V .

2.1 Plücker Coordinates

Let U be a k -dimensional subspace of the $(m+1)$ -dimensional vector space V , and $\{u_1, u_2, \dots, u_k\}$ a basis of it. When these vectors are arranged as rows of a matrix, we obtain:

$$\begin{pmatrix} u_{1,1} & u_{1,2} & \cdots & u_{1,m} & 1 \\ u_{2,1} & u_{2,2} & \cdots & u_{2,m} & 1 \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ u_{k,1} & u_{k,2} & \cdots & u_{k,m} & 1 \end{pmatrix}.$$

The $(j_1, j_2, \dots, j_k)$ -th *Plücker coordinate* of the subspace U , denoted by $P_{j_1, j_2, \dots, j_k}$, is the $k \times k$ determinant formed by the k columns of the above matrix with indices $j_1, j_2, \dots, j_k$. Since we have a

Plücker coordinate for each combination of the k columns, the total number of Plücker coordinates is $\binom{m+1}{k}$. The *Plücker coordinate vector* of the subspace U is the vector P_U that contains in some predetermined order its Plücker coordinates. U uniquely determines P_U up to a scalar multiple.

The Plücker coordinate vector of the line Λ passing through points a and b , represented in homogeneous coordinates by the rows of

$$\begin{pmatrix} a_1 & a_2 & a_3 & 1 \\ b_1 & b_2 & b_3 & 1 \end{pmatrix},$$

is defined as:

$$P_\Lambda = (-P_{1,4}, -P_{2,4}, -P_{3,4}, P_{2,3}, -P_{1,3}, P_{1,2})^t = (b_1 - a_1, b_2 - a_2, b_3 - a_3, a_2 b_3 - a_3 b_2, a_3 b_1 - a_1 b_3, a_1 b_2 - a_2 b_1)^t = (\mathbf{S}, \mathbf{r} \times \mathbf{S})^t$$

where $\mathbf{S} = \mathbf{b} - \mathbf{a}$, $(\mathbf{r} \times \mathbf{S})$ represents the moment of Λ with respect to the origin, and $\mathbf{r}$ is any point on the line. The vector P_Λ is determined by Λ up to a scalar multiple. It is convenient to normalize it such that $\mathbf{S} \cdot \mathbf{S} = 1$ as it will be used to represent rotations.

The point at infinity on Λ has homogeneous coordinates $(b_1 - a_1, b_2 - a_2, b_3 - a_3, 0)^t$ and can be thought as infinitely far away in the direction given by $\mathbf{S}$.

A line at infinity is determined by two distinct points, c and d , at infinity represented by the rows of

$$\begin{pmatrix} c_1 & c_2 & c_3 & 0 \\ d_1 & d_2 & d_3 & 0 \end{pmatrix}$$

whose Plücker coordinate vector is

$$P_\Lambda = (0, 0, 0, c_2 d_3 - c_3 d_2, c_3 d_1 - c_1 d_3, c_1 d_2 - c_2 d_1)^t = (0, 0, 0, \mathbf{r} \times \mathbf{S})^t.$$

Since lines at infinity will be used to represent translations, it is convenient to normalize this vector in such a way that $(\mathbf{r} \times \mathbf{S}) \cdot (\mathbf{r} \times \mathbf{S}) = 1$.

The Plücker coordinate vector of the plane Π , determined by three finite points whose homogeneous coordinates are the rows of

$$\begin{pmatrix} a_1 & a_2 & a_3 & 1 \\ b_1 & b_2 & b_3 & 1 \\ p_1 & p_2 & p_3 & 1 \end{pmatrix},$$

is defined as

$$P_\Pi = (P_{2,3,4}, -P_{1,3,4}, P_{1,2,4}, P_{1,2,3})^t = (\mathbf{N}, \mathbf{r} \cdot \mathbf{N})^t,$$

where $\mathbf{N}$ is a normal vector to Π and $\mathbf{r}$ is the position vector of any point on Π .

2.2 Dual Plücker Coordinates

Let U be a k -dimensional subspace of the $(m+1)$ -dimensional vector space V and $\{u_1, u_2, \dots, u_k\}$ a basis of it. We can construct the dual of the vector subspace U as follows. Consider the linear system of equations

$$\sum_{j=0}^{m+1} x_j u_{h,j} = 0, \quad h = 1, 2, \dots, k.$$

Since its matrix has rank k its solution space is a $(m+1-k)$ -dimensional vector space U^* . Let $\{w_1, w_2, \dots, w_{m+1-k}\}$ be a basis of U^* . Then, we have the following relationships between the basis vectors of U and U^*

$$\sum_{j=0}^{m+1} w_{i,j} u_{h,j} = 0, \quad i = 1, 2, \dots, (m+1-k), \quad h = 1, 2, \dots, k \quad (1)$$

by which we can compute the basis of U^* from the basis of U up to a scalar multiple. The vector spaces U and U^* are said to be *dual spaces*. Thus, the *dual Plücker coordinate vector* of U is defined to be the vector that contains the Plücker coordinates of U^* , called *dual Plücker coordinates* of U .

It can be proved that the number of dual Plücker coordinates equals the number of Plücker coordinates, the only difference between them being their ordering and some sign changes. For example, the Plücker coordinate vector of a line in $\mathbb{R}^3$ has the first three and the last three elements interchanged with respect to the dual Plücker coordinate vector of the same line.

If we replace vectors of V by hyperplanes we obtain its dual vector space V^* .

2.3 The Join and Meet Operators

Let V be a n -dimensional vector space over the field $\mathbb{R}$, U a k -dimensional subspace of V , and $\{u_1, u_2, \dots, u_k\}$ a basis of it. Let also P be the Plücker coordinate vector of U , that is, a vector in the $\binom{n}{k}$ -dimensional vector space $V^{(k)}$. The vector P is called *k-extensor* or *decomposable k-tensor* and is denoted by

$$P = \vee(u_1 u_2 \dots u_k) = u_1 \vee u_2 \vee \dots \vee u_k.$$

The vector space $V^{(k)}$ also contains *indecomposable k-tensors* which can always be rewritten as linear combination of *k-extensors*.

The subspace U , also denoted by $\bar{P}$, is defined as the *support* of P and the scalar k is defined to be the *step* of the extensor. Two *k-extensors* are equal up to a scalar multiple if, and only if, they have the same support.

Let $A = a_1 \vee a_2 \vee \dots \vee a_k$ and $B = b_1 \vee b_2 \vee \dots \vee b_j$ be two extensors. The *join* of A and B is defined as the $(j+k)$ -extensor

$$A \vee B = a_1 \vee a_2 \vee \dots \vee a_k \vee b_1 \vee b_2 \vee \dots \vee b_j.$$

If the vectors $\{a_1, a_2, \dots, a_k, b_1, b_2, \dots, b_j\}$ are linearly dependent, then $A \vee B = 0$. If they are independent,

$$\overline{A \vee B} = \bar{A} + \bar{B} = \text{span}(\bar{A} \cup \bar{B}). \quad (2)$$

This means that the join of two extensors represent the operation of joining the associated vector subspaces.

Now, another operation that plays a similar role for the intersection of subspaces is defined. Let A and B be the above two extensors with $(k+j) \geq n$. The *meet* of A and B is defined as:

$$A \wedge B = \sum_{\sigma} \text{sgn}(\sigma) [a_{\sigma(1)}, \dots, a_{\sigma(n-j)}, b_1, \dots, b_j] \quad (3)$$

$$a_{\sigma(n-j+1)} \vee a_{\sigma(n-j+2)} \vee \dots \vee a_{\sigma(k)} \quad (3)$$

where the brackets stand for determinants and the sum is taken over all the permutations σ of $\{1, 2, \dots, k\}$ such that $\sigma(1) < \sigma(2) < \dots < \sigma(n-j)$ and $\sigma(n-j+1) < \sigma(n-j+2) < \dots < \sigma(k)$. This formula, called the *shuffle formula*, is a useful tool in practical applications.

It can be proved that if $A \neq 0$ and $B \neq 0$ and $\bar{A} \cup \bar{B}$ spans V , then

$$\overline{A \wedge B} = \bar{A} \cap \bar{B}. \quad (4)$$

An important property is that $\vee$ and $\wedge$ are dual operators. If we interchange $\vee$ and $\wedge$ we must interchange $V^{(k)}$ with $V^{*(n-k)}$.

The vector spaces $V^{(k)}$ can be combined into another vector space over $\mathbb{R}$,

$$\Lambda(V) = V^{(0)} \oplus V^{(1)} \oplus \dots \oplus V^{(n)}$$

where $V^{(0)}$ and $V^{(n)}$ both coincide with $\mathbb{R}$. The elements of $\Lambda(V)$ are all tensors, that is, arbitrary linear combinations of extensors of various steps. We have that $\dim(\Lambda(V)) = \sum_{k=0}^n \binom{n}{k} = 2^n$.

The Grassmann-Cayley Algebra is defined as the vector space $\Lambda(V)$ with the operations $\vee$ and $\wedge$. These operations are both associative, distributive over addition, and anticommutative.

3 Projective Representation of Twists and Wrenches

If $\mathbf{v}$ is the velocity of the Euclidean point $\mathbf{p}$, then the *motion* of the projective point p can be defined as $M(p) = (\mathbf{v}, \mathbf{p} \cdot \mathbf{v})^t$.

If a and b are finite projective points, for each point p in space we can express this motion in projective terms as $M(p) = (\mathbf{v}, \mathbf{p} \cdot \mathbf{v})^t = a \vee b \vee p$. The 2-extensor $a \vee b$, that represents the line passing through a and b , is called the *center of the motion*. Since $M(a) = 0$ and $M(b) = 0$, it can be used to represent a *rotation* about the axis determined by a and b .

A *translation* can be described as a rotation about an axis at infinity. Let $c = (c_1, c_2, c_3, 0)^t$ and $d = (d_1, d_2, d_3, 0)^t$ be two points at infinity, then the extensor $c \vee d$ can be used as the center of motion such that $M(p) = c \vee d \vee p$. The corresponding velocity is $\mathbf{v} = (c_2 d_3 - c_3 d_2, c_3 d_1 - c_1 d_3, c_1 d_2 - c_2 d_1)^t$. Since it is independent from the point p , it can be effectively used to represent a translation.

With a serial composition of translations and rotations a more general screw motion in space can be obtained. This motion is represented by a *twist* $t = (\omega, \mathbf{v})^t$, where ω and $\mathbf{v}$ represent an angular velocity vector and a linear velocity vector, respectively. In general, a twist cannot be represented using the join of two projective points. Indeed it is an indecomposable 2-tensor that can be expressed as linear combination of 2-extensors. Moreover, according to the Chasles's theorem it can be expressed as the composition of a translation along an axis and a rotation about the same axis. Instantaneously, the serial composition of twists corresponds to their addition.

A vector $\mathbf{f} = (f_1, f_2, f_3)^t$ that represents an Euclidean *force* applied at the Euclidean point $\mathbf{p} = (p_1, p_2, p_3)^t$ can be represented in the projective space by the join of the two projective points $p = (p_1, p_2, p_3, 1)^t$ and $f = (f_1, f_2, f_3, 0)^t$, that is, by the extensor $F = p \vee f = (\mathbf{f}, \mathbf{p} \times \mathbf{f})^t$. If we have a set of forces $F_i = p \vee f_i$ applied at a given point p , the resultant, $\mathbf{G}$, can be obtained by adding the free vectors f_i and applying the result at p , that is, $G = \sum_i (p \vee f_i) = p \vee (\sum_i f_i)$.

If two forces $F_1 = p \vee f$ and $F_2 = q \vee g$ with $\mathbf{f} = -\mathbf{g}$ are applied to two distinct points p and q , the resultant $G = F_1 + F_2 = p \vee f + q \vee g = p \vee f + q \vee (-f) = (p - q) \vee f$ is called a *couple*. Since $p - q = (p_1 - q_1, p_2 - q_2, p_3 - q_3, 0)^t$ is a point at infinity, a couple can be thought as a force at infinity.

In general, the composition of forces in space does not correspond to a single new force and cannot be expressed using the extensor of two projective points. Their resultant is a *wrench* $w = (\mathbf{f}, \mathbf{m})^t$, where $\mathbf{f}$ and $\mathbf{m}$ are a force vector and a moment vector, respectively. In general a wrench is an indecomposable 2-tensor which can be expressed in terms of 2-extensor. Moreover, according to Poincot's theorem a wrench can always be rewritten as a composition of a force along a line

and a couple on the plane normal to the line.

Twists will be represented as linear combinations of 2-extensors of $V^{(2)}$ while wrenches will be represented in terms of the 2-extensors of its dual space $V^{*(2)}$.

Instantaneously, the resultant of the parallel composition of wrenches corresponds to their addition.

4 Reciprocity

Let us consider our rigid body M partially constrained by the static environment S . We define the *twist space* $\mathbf{T}$ of M as the vector space of all possible instantaneous twists that it can have with reference to S , and we define its *wrench space* $\mathbf{W}$ as the vector space of all reaction wrenches that can be generated in the interaction between M and S .

Since the set of established contacts between M and S cannot be broken, any twist $t \in \mathbf{T}$ of M must be *reciprocal* to any wrench $w \in \mathbf{W}$ between M and S because the power generated by t and w must be zero (see [12]), that is,

$$\omega \cdot \mathbf{m} + \mathbf{v} \cdot \mathbf{f} = 0.$$

This relation is nothing more than the expression of the pairing of the vector spaces $V^{(2)}$ and its dual $V^{*(2)}$ as expressed by (1). Thus, we can say that twist and wrench spaces of a partially constrained rigid body are dual spaces in the sense of Sect. 2.2.

If the twist space of M is the entire $V^{(2)}$, it has full mobility while, if its wrench space is the whole $V^{*(2)}$, it can apply any wrench to S . In general, since the twist space is a subspace of $V^{(2)}$ and the wrench space is a subspace of $V^{*(2)}$, it is convenient to set $V^{(2)} = H$ and work in the Grassmann-Cayley Algebra $\Lambda(H)$ over this auxiliary vector space in which 2-extensors of $V^{(2)}$ become 6-dimensional vectors.

It is well known (see, for example, [4]) that the twist (wrench) space of the serial (parallel) combination of motion constraints is the sum of the twist (wrench) spaces of the composing constraints. Analogously, the twist (wrench) space of the parallel (serial) combination of motion constraints is the intersection of the twist (wrench) spaces of the composing constraints. It is important to point out that the reciprocity relation remains valid under serial and parallel combination of motion constraints.

These considerations can be re-formulated in the language of the Grassmann-Cayley algebra. From properties (2) and (4) of the join and meet operators it follows that:

- The twist (wrench) space of the serial (parallel) connection of motion constraints is the support of

Figure 1: The principal frame of the smooth surface S_i at point c_i

the join of the extensors that represent the twist (wrench) spaces of the composing constraints, provided that their twist (wrench) extensors are linearly independent.

- The twist (wrench) space of the parallel (serial) connection of motion constraints is the support of the meet of the extensors that represent the twist (wrench) spaces of the composing constraints, provided that the sum of the composing twist (wrench) spaces spans H (H^*).

This considerations will be applied to the study of the kinematic chains that instantaneously are equivalent to the contact between M and S .

5 A Kinematic Model of Point Contacts

The maximum and minimum curvature directions at a point on a smooth surface are always orthogonal [2] and can be used to define a reference frame called the *principal frame* (Fig. 1) in which the x axis is directed along the direction of maximum curvature, the y axis along the direction of minimum curvature, and the z axis is directed inward. These axes are uniquely defined unless the point is an umbilic, that is, a point in which the curvature is the same in all directions.

Let us suppose that M and S are in contact at point c_i and that their boundaries can be represented, in a neighbourhood of this point, by two smooth surface patches $\mathcal{M}_i$ and S_i . Let Π_i be the plane tangent to both surfaces at c_i . Since it has been assumed that

there is no friction between M and S , the situation can be kinematically modelled with the kinematic chain represented in Fig. 2 that instantaneously preserves the contact and gives the same motion freedom as the physical contact. Such a motion can be thought as the composition of a *slip* motion of M in which the contact point does not move with respect to S_i , a rotation of M that do not change the contact point with respect both S_i and $\mathcal{M}_i$ and, finally, a *slide* motion of M in which the contact point do not move over $\mathcal{M}_i$ [4].

The slip joint can be kinematically modelled by two revolute joints, $R_{min}^{S_i}$ and $R_{max}^{S_i}$, located at the centers of minimum and maximum curvature of S_i whose axes are parallel to the direction of maximum and minimum curvature of S_i , respectively.

The rotation of M can be modelled with a revolute joint $R^{S_i, \mathcal{M}_i}$ whose axis is normal to plane Π_i and the slide joint can be represented by means of two revolute joints, $R_{min}^{\mathcal{M}_i}$ and $R_{max}^{\mathcal{M}_i}$, located at the centers of minimum and maximum curvature of the surface $\mathcal{M}_i$ that have axes parallel to the directions of maximum and minimum curvature of $\mathcal{M}_i$, respectively.

In order to model the resulting kinematic chain using the elements of the Grassmann-Cayley Algebra, let us first define a reference frame, F_i , at the contact point c_i such that:

$$x_{F_i} = \begin{pmatrix} \cos(\alpha) & -\sin(\alpha) & 0 & 0 \\ \sin(\alpha) & \cos(\alpha) & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} x_{\mathcal{M}_i}, \text{ and}$$

$$x_{F_i} = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} x_{S_i}$$

are the transformations relating the principal frames of both surfaces and F_i .

The center of motion of $R_{min}^{S_i}$ is the axis parallel to x_{S_i} passing through the point $(x_{S_i}, y_{S_i}, z_{S_i}, 1) = (0, 0, r_{max}^{S_i}, 1)$ which, when expressed in the reference frame F_i , leads to the following extensor:

$$L_{min}^{S_i} = \vee \begin{pmatrix} 0 & 0 & -r_{max}^{S_i} & 1 \\ -1 & 0 & -r_{min}^{S_i} & 1 \end{pmatrix} = (-1, 0, 0, 0, r_{max}^{S_i}, 0).$$

The center of motion of $R_{max}^{S_i}$ is the axis parallel to y_{S_i} passing through the point $(x_{S_i}, y_{S_i}, z_{S_i}, 1) = (0, 0, r_{min}^{S_i}, 1)$. The corresponding extensor is:

$$L_{max}^{S_i} = \vee \begin{pmatrix} 0 & 0 & -r_{min}^{S_i} & 1 \\ 0 & -1 & -r_{max}^{S_i} & 1 \end{pmatrix} = (0, -1, 0, 0, -r_{min}^{S_i}, 0).$$

Figure 2: Kinematic model of a surface-surface contact

The center of motion of $R^{S_i, \mathcal{M}_i}$ is the axis parallel to $z_{\mathcal{M}_i}$ passing through the point $(x_{\mathcal{M}_i}, y_{\mathcal{M}_i}, z_{\mathcal{M}_i}, 1) = (0, 0, 0, 1)$. The corresponding extensor is

$$L^{S_i, \mathcal{M}_i} = \vee \begin{pmatrix} 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 1 \end{pmatrix} = (0, 0, 1, 0, 0, 0).$$

The center of motion of $R_{max}^{\mathcal{M}_i}$ is an axis parallel to $y_{\mathcal{M}_i}$ passing through the point $(x_{\mathcal{M}_i}, y_{\mathcal{M}_i}, z_{\mathcal{M}_i}, 1) = (0, 0, r_{min}^{\mathcal{M}_i}, 1)$ that, when expressed in the reference frame F_i , corresponds to an axis having the direction of the vector $(-\sin(\alpha_i), \cos(\alpha_i), 0, 1)$ and passing through the point $(x_{F_i}, y_{F_i}, z_{F_i}, 1) = (0, 0, r_{min}^{\mathcal{M}_i}, 1)$. The

corresponding extensor is:

$$L_{max}^{\mathcal{M}_i} = \vee \begin{pmatrix} 0 & 0 & r_{min}^{\mathcal{M}_i} & 1 \\ -\sin(\alpha_i) & \cos(\alpha_i) & r_{min}^{\mathcal{M}_i} & 1 \end{pmatrix} = (-\sin(\alpha_i), \cos(\alpha_i), 0, -r_{min}^{\mathcal{M}_i} \cos(\alpha_i), -r_{min}^{\mathcal{M}_i} \sin(\alpha_i), 0).$$

The center of motion of $R_{min}^{\mathcal{M}_i}$ is an axis parallel to $x_{\mathcal{M}_i}$ passing through the point $(x_{\mathcal{M}_i}, y_{\mathcal{M}_i}, z_{\mathcal{M}_i}, 1) = (0, 0, r_{max}^{\mathcal{M}_i}, 1)$ that, when expressed in the reference frame F_i , corresponds to an axis having the direction of the vector $(-\cos(\alpha_i), -\sin(\alpha_i), 0, 1)$ and passing through the point $(x_{F_i}, y_{F_i}, z_{F_i}, 1) = (0, 0, r_{max}^{\mathcal{M}_i}, 1)$. The corresponding extensor is:

$$L_{min}^{\mathcal{M}_i} = \vee \begin{pmatrix} 0 & 0 & r_{max}^{\mathcal{M}_i} & 1 \\ -\cos(\alpha_i) & -\sin(\alpha_i) & r_{max}^{\mathcal{M}_i} & 1 \end{pmatrix} = (-\cos(\alpha_i), -\sin(\alpha_i), 0, r_{max}^{\mathcal{M}_i} \sin(\alpha_i), -r_{max}^{\mathcal{M}_i} \cos(\alpha_i), 0).$$

If in the above contact model $r_{max}^{S_i}$ is set to ∞ , $R_{min}^{S_i}$ becomes a translational joint, i.e. a rotation at infinity, with axis parallel to x_{S_i} . Using the points at infinity $(x_{S_i}, y_{S_i}, z_{S_i}, 0) = (0, 0, 1, 0)$ and $(x_{S_i}, y_{S_i}, z_{S_i}, 0) = (1, 0, 1, 0)$, the corresponding center of motion can be expressed in the frame F_i by the following extensor

$$L_{min}^{S_i} = \vee \begin{pmatrix} 0 & 0 & -1 & 0 \\ 1 & 0 & -1 & 0 \end{pmatrix} = (0, 0, 0, 0, 1, 0).$$

Thus, the presented model is general enough to represent, for example, the edge-edge or vertex-face contacts arising when dealing with polyhedra.

6 Multiple Contacts

When M keeps several contacts with S , a kinematic chain for each contact must be introduced. The extensors have to be referred to the same reference frame, say F_0 , and the resulting parallel mechanism can be analyzed using the join and meet operators.

If the extensors $L_{min}^{S_i}, L_{max}^{S_i}, L^{S_i, \mathcal{M}_i}, L_{max}^{\mathcal{M}_i}, L_{min}^{\mathcal{M}_i}$ are linearly independent, the twist space $\mathbf{T}_i$ of the link i is the support of the 5-extensor $L_i = L_{min}^{S_i} \vee L_{max}^{S_i} \vee L^{S_i, \mathcal{M}_i} \vee L_{max}^{\mathcal{M}_i} \vee L_{min}^{\mathcal{M}_i}$ of $H^{(5)}$, that is,

$$\mathbf{T}_i = \overline{L_i} = \overline{L_{min}^{S_i} \vee L_{max}^{S_i} \vee L^{S_i, \mathcal{M}_i} \vee L_{max}^{\mathcal{M}_i} \vee L_{min}^{\mathcal{M}_i}}$$

where $L_{min}^{S_i}, L_{max}^{S_i}, L^{S_i, \mathcal{M}_i}, L_{max}^{\mathcal{M}_i}$ and $L_{min}^{\mathcal{M}_i}$ are vectors of H .

The wrench space $\mathbf{W}_i$ of the link i is its dual, that is, the support of the vector $L_i^* = (L_{min}^{S_i} \vee L_{max}^{S_i} \vee L^{S_i, \mathcal{M}_i} \vee L_{max}^{\mathcal{M}_i} \vee L_{min}^{\mathcal{M}_i})^*$.

Figure 3: Three contacts between M and S and the instantaneously equivalent kinematic chain

$L_{max}^{\mathcal{M}_i} \vee L_{min}^{\mathcal{M}_i})^* = L_{min}^{S_i} \wedge L_{max}^{S_i} \wedge L^{S_i, \mathcal{M}_i} \wedge L_{max}^{\mathcal{M}_i} \wedge L_{min}^{\mathcal{M}_i}$ of H^* , that is,

$$\mathbf{W}_i = \overline{L_i^*} = \overline{L_{min}^{S_i} \wedge L_{max}^{S_i} \wedge L^{S_i, \mathcal{M}_i} \wedge L_{max}^{\mathcal{M}_i} \wedge L_{min}^{\mathcal{M}_i}}$$

where the extensors $L_{min}^{S_i}$, $L_{max}^{S_i}$, $L^{S_i, \mathcal{M}_i}$, $L_{max}^{\mathcal{M}_i}$ and $L_{min}^{\mathcal{M}_i}$ are 5-extensors of $H^{(5)}$.

Suppose that M and S make $k \leq 6$ contacts and let $L_1, L_2, \dots, L_k$ be the extensors of the kinematic chains that are instantaneously equivalent to each one of them.

The twist space $\mathbf{T}$ of M constrained to keep the established contacts with S is the support of the extensor $L = L_1 \wedge L_2 \wedge \dots \wedge L_k$, that is,

$$\mathbf{T} = \overline{L} = \overline{L_1 \wedge L_2 \wedge \dots \wedge L_k}.$$

Since M can apply forces to S only in one direction, the space $\mathbf{W}$ of possible wrenches between M and S does not coincide with the wrench space of its instantaneously equivalent kinematic chain. It is a subspace of the support of the extensor $L^* = L_1^* \vee L_2^* \vee \dots \vee L_k^*$, that is,

$$\mathbf{W} \subset \overline{L^*} = \overline{L_1^* \vee L_2^* \vee \dots \vee L_k^*}. \quad (5)$$

It is easy to take this fact into account by appropriately choosing the signs of the coefficients of the linear combination of the wrench extensors in (5).

7 An Example

Let us consider the situation represented in Fig. 3 in which the moving body M makes three point contacts with the static environment S .

The twist space $\mathbf{T}$ of the parallel mechanism is the support of $L = L_1 \wedge L_2 \wedge L_3$. The meet operator is associative, thus we can compute first the meet L' between L_1 and L_2 and then the meet of L' with L_3 . The shuffle formula gives

$$\begin{aligned} L' &= L_1 \wedge L_2 = \\ &+ [L_{\min}^{S_1} L_{\min}^{S_2} L_{\max}^{S_2} L_{\max}^{S_2, M_2} L_{\max}^{M_2} L_{\min}^{M_2}] L_{\max}^{S_1, M_1} \vee L_{\max}^{S_1, M_1} \vee L_{\max}^{M_1} \vee L_{\min}^{M_1} \\ &- [L_{\max}^{S_1} L_{\min}^{S_2} L_{\max}^{S_2} L_{\max}^{S_2, M_2} L_{\max}^{M_2} L_{\min}^{M_2}] L_{\min}^{S_1, M_1} \vee L_{\min}^{S_1, M_1} \vee L_{\max}^{M_1} \vee L_{\min}^{M_1} \\ &+ [L_{\min}^{S_1, M_1} L_{\min}^{S_2} L_{\max}^{S_2} L_{\max}^{S_2, M_2} L_{\max}^{M_2} L_{\min}^{M_2}] L_{\min}^{S_1} \vee L_{\max}^{S_1} \vee L_{\max}^{M_1} \vee L_{\min}^{M_1} \\ &- [L_{\max}^{S_1, M_1} L_{\min}^{S_2} L_{\max}^{S_2} L_{\max}^{S_2, M_2} L_{\max}^{M_2} L_{\min}^{M_2}] L_{\min}^{S_1} \vee L_{\max}^{S_1} \vee L_{\min}^{M_1} \vee L_{\min}^{M_1} \\ &+ [L_{\min}^{S_1} L_{\min}^{S_2} L_{\max}^{S_2} L_{\max}^{S_2, M_2} L_{\max}^{M_2} L_{\min}^{M_2}] L_{\min}^{S_1} \vee L_{\max}^{S_1} \vee L_{\min}^{M_1} \vee L_{\max}^{M_1} \\ &= \rho_1 L'_1 + \rho_2 L'_2 + \rho_3 L'_3 + \rho_4 L'_4 + \rho_5 L'_5, \end{aligned}$$

where L'_i is the i -th 4-extensor of the above expression and ρ_i is the value of the corresponding determinant. Since the meet operation is distributive over addition we can write $L = L' \wedge L_3 = \rho_1 L'_1 \wedge L_3 + \rho_2 L'_2 \wedge L_3 + \rho_3 L'_3 \wedge L_3 + \rho_4 L'_4 \wedge L_3 + \rho_5 L'_5 \wedge L_3$ where, for example,

$$\begin{aligned} L'_1 \wedge L_3 &= \\ &+ [L_{\max}^{S_1} L_{\min}^{S_3} L_{\max}^{S_3} L_{\max}^{S_3, M_3} L_{\max}^{M_3} L_{\min}^{M_3}] L_{\max}^{S_1, M_1} \vee L_{\max}^{M_1} \vee L_{\min}^{M_1} \\ &- [L_{\min}^{S_1, M_1} L_{\min}^{S_3} L_{\max}^{S_3} L_{\max}^{S_3, M_3} L_{\max}^{M_3} L_{\min}^{M_3}] L_{\max}^{S_1} \vee L_{\max}^{M_1} \vee L_{\min}^{M_1} \\ &+ [L_{\max}^{S_1} L_{\min}^{S_3} L_{\max}^{S_3} L_{\max}^{S_3, M_3} L_{\max}^{M_3} L_{\min}^{M_3}] L_{\max}^{S_1} \vee L_{\min}^{S_1, M_1} \vee L_{\min}^{M_1} \\ &- [L_{\min}^{S_1} L_{\min}^{S_3} L_{\max}^{S_3} L_{\max}^{S_3, M_3} L_{\max}^{M_3} L_{\min}^{M_3}] L_{\max}^{S_1} \vee L_{\min}^{S_1, M_1} \vee L_{\max}^{M_1}. \end{aligned}$$

The meet between $L'_i, i = 2, \dots, 5$ and L_3 can be computed in a similar way.

The space $\mathbf{W}$ of possible wrenches between M and S is a subspace of the support of the 3-extensor $L^* = L_1^* \vee L_2^* \vee L_3^*$.

8 Conclusions

In this paper a new framework for the analysis of frictionless rigid body interactions has been presented. It is based on the Grassmann-Cayley Algebra by means of which the kinematic properties of the parallel mechanism resulting from the substitution of each contact by its instantaneously equivalent second order approximation have been studied.

It has been shown that the structure of this algebra fits perfectly to the kinematic analysis of rigid body interactions due to the kinematic interpretation of the concept of extensor, the existence of an explicit formula for the meet operator and the presence of an intrinsic duality that corresponds to the reciprocity condition between twist and wrench spaces of partially constrained rigid bodies.

This analysis has been carried out with the implicit hypothesis of the absence of uncertainties in the

geometric models of the objects involved in the motion but it is also possible to use more general frameworks that include the Grassmann-Cayley Algebra as a subalgebra such as the *Grassmann Algebra* and the *Clifford Algebra*. Since these algebras are endowed with a metrics, by means of them it is also possible to deal with geometric uncertainties.

References

- [1] E. Staffetti, L. Ros, and F. Thomas, "Finding infinitesimal motions of objects in assemblies using Grassmann-Cayley algebra," in *Proc. of the Tenth World Congress on the Theory of Machines and Mechanisms*, pp. 584-591, 1999.
- [2] B. O. Neill, *Elementary Differential Geometry*. Academic Press, 1966.
- [3] J.-P. Thirion and A. Gourdon, "The marching lines algorithm: new results and proofs," Rapport de Recherche 1881, INRIA, April 1993.
- [4] H. Bruyninckx, S. Demey, S. Dutré, and J. De Schutter, "Kinematic models for model-based compliant motion in the presence of uncertainty," *The International Journal of Robotics Research*, vol. 14, no. 5, pp. 465-482, 1995.
- [5] E. Staffetti and F. Thomas, "Kinematic analysis of serial and parallel robot manipulators using Grassmann-Cayley algebra," in *Advances in Robot Kinematics* (J. Lenarčič and M. M. Stanisic, eds.), Kluwer Academic Publishers, 2000.
- [6] M. Barnabei, A. Brini, and G.-C. Rota, "On the exterior calculus of invariant theory," *Journal of Algebra*, vol. 96, pp. 120-160, 1985.
- [7] N. White, "A tutorial on Grassmann-Cayley algebra," in *Invariant Methods in Discrete and Computational Geometry* (N. White, ed.), pp. 93-106, Kluwer Academic Publisher, 1995.
- [8] N. White, "Grassmann-Cayley algebra and robotics," *Journal of Intelligent Robotics Systems*, vol. 11, pp. 91-107, 1994.
- [9] N. White, "Geometric applications of the Grassmann-Cayley algebra," in *Handbook of Discrete and Computational Geometry* (J. E. Goodman and J. O'Rourke, eds.), CRC Press, 1997.
- [10] R. S. Ball, *A Treatise on the Theory of Screws*. Cambridge University Press, 1900.
- [11] K. H. Hunt, *Kinematic Geometry of Mechanisms*. Oxford Science Publications, 1990.
- [12] J. Duffy, "The fallacy of modern hybrid control theory that is based on "orthogonal complements" of twist and wrench spaces," *Journal of Robotic Systems*, vol. 7, no. 2, pp. 139-144, 1990.