ENVIRONMENTAL RESEARCH COMMUNICATIONS

LETTER • OPEN ACCESS

A mechanistic assessment of the potential ecological risk to seagrass meadows posed by marine echosounders

To cite this article: A Alvarez 2020 Environ. Res. Commun. 2 011002

View the article online for updates and enhancements.

You may also like

- Analysis of angular resolution and range resolution on multibeam echosounder R2 Sonic 2020 in Port of Tanjung Perak (Surabaya) R N A Oktavia, D G Pratomo and Khomsin
- On the investigation of vertical uncertainty of depth sounding in a shallow environment with muddy seabed: Preliminary results from a launch operation of a dual-frequency echosounder G Alodia, F Muhammad and Poerbandono
- Targets strength of freshwater fish with single beam echosounder S Pujiyati, P E Karo-Karo, A Y N Yaman et al.

Environmental Research Communications

LETTER

OPEN ACCESS

CrossMark

RECEIVED 11 July 2019

REVISED 20 October 2019

ACCEPTED FOR PUBLICATION 13 November 2019

PUBLISHED 28 November 2019

Original content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence.

Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.



A mechanistic assessment of the potential ecological risk to seagrass meadows posed by marine echosounders

A Alvarez 💿

Department of Marine Ecology (MARE), Instituto Mediterraneo de Estudios Avanzados-IMEDEA (CSIC-UIB), C/Miquel Marques 21, 07190 Esporlas, Spain

E-mail: alberto.alvarez@imedea.uib-csic.es

Keywords: seagrass, echosounder, ultrasound, Halodule wrightii, Syringodium filiforme

Abstract

Motivated by experimental evidence, a mechanistic model is used to investigate the impact of marine echosounder transmissions on seagrass leaves. The interaction of the ultrasonic field with the seagrass is solved within the leaf cross-section. The leaf tissue is assumed to be elastic, homogeneous and isotropic, with embedded cavities representing lacunae. A standard Galerkin finite element method is employed to numerically solve the resulting equations. Natural vibration frequencies are computed for leaves of *Halodule wrightii* and *Syringodium filiforme*. Strong perturbations in the leaf structure are expected when natural and echosounder frequencies match. The results reveal that a significant number of natural frequencies are within or near the typical frequency bands of echosounder operations. In addition, stresses in the leaf tissue of seagrass at 20 m depth were computed in a typical scenario for echosounder operations. Leaf-tissue damage in S. *filiforme* could result under these conditions. Within the framework of the theoretical assumptions, the results highlight the potential and, until now, unnoticed risks to seagrass meadows posed by marine echosounders.

1. Introduction

Seagrasses are a key component of many marine coastal regions worldwide (Orth *et al* 2006). Ecologically, they constitute the habitat of diverse species (Duffy 2006, Heck *et al* 2008), improve the water quality conditions in coastal regions (Denninson *et al* 1993, McGlathery *et al* 2007) and represent an important carbon sink (Duarte *et al* 2005, Fourqurean *et al* 2012) and nitrogen cycler (Zarnoch *et al* 2017) in marine areas. Seagrass meadows are not exempted of anthropogenic disturbances in coastal environments which have resulted in reductions in their populations (Duarte 2002, Orth *et al* 2006, Waycott *et al* 2009). Degradation of water quality, increased loading of sediment, contaminants and nutrients from both diffuse and point sources, eutrophication, introduction of nonnative species and dredging and boating effects are some anthropogenic stressors behind seagrass declines (Orth *et al* 2006). The identification and quantification of the different anthropogenic pressures on seagrass meadows is required for their present and future preservation. Unfortunately, relevant anthropogenic stressors on seagrass meadows may remain unnoticed.

Seagrass leaves generally present a large number of areal spaces, or lacunae, surrounded by mesophyll tissue (Kuo and den Hartog 2006). Lacunae allow the accumulation and pressure-driven flow of gases resulting from photosynthetic activity. These cavities interconnect all vegetative and reproductive organs in the seagrass, but the cavities are interrupted by septa between organs (Kuo and den Hartog 2006). Lacunae differ in cross-sectional size (hundreds of μ m) and shape (circular to elliptical) among species (Kuo and den Hartog 2006, Wilson and Dunton 2009). These areal spaces comprise 4% to 30% of the leaf cross-sectional area (Grice *et al* 1996).

Gas bodies in biological tissues can energetically pulsate when insonified under suitable conditions, a phenomenon termed gas-body activation (Miller 1977). Despite the terminology, these oscillations are often associated more with the natural vibration modes and frequencies of the elastic structure where the cavity is



embedded than with the pulsation of gas (Miller 1984). Under external periodic excitation at natural frequencies, the structural vibration amplitudes increase significantly (resonance), which, due to the occurrence of stresses with a large absolute magnitude, can lead to a decrease in strength, cracking, or even destruction of the biological tissue near the cavity wall. Specifically, Miller and Thomas (1993) experimentally found that ultrasonic activation of gas channels enclosed by cell walls in *Elodea* leaves resulted in plant-tissue damage. Due to the small size of these gas bodies (approximately 10 μ m), the ultrasound frequencies ranged from 0.7 to 15 MHz. The observed thresholds for plant-tissue damage ranged from 50 Pa and 6 kPa for ultrasound durations of 5 min and 30 s, respectively (Miller and Thomas 1993). Similarly, gas-body activation of lacunae in seagrass leaves can occur if the marine environment is insonified with frequencies (>80 kHz) during seafloor acoustic surveys provides indirect evidence of gas-body activation (Lyons and Abraham 1999, McCarthy, Sabol (2000), Komatsu *et al* 2003).

Echosounders are widespread acoustic devices used for hydrography, seafloor mapping, fish-finding and navigation safety. These acoustic systems operate at frequencies with typical values of 12, 24, 30, 38, 50, 80, 100, 120 or 200 kHz. (Lurton and DeRuiter 2011). Low (high) frequencies are usually selected in deep (shallow) water operations. Systems dedicated to very shallow water depths (few metres) can operate at nominal frequencies above 200 kHz (300, 400 or 450 kHz; Lurton 2016). The associated bandwidths are approximately 10 kHz. The transmission geometry is described by a main lobe of acoustic radiation with a small angular aperture (5° to 15°) and spurious sidelobes 20 dB to 30 dB below the intensity of the main lobe. The maximal transmit power may be as high as 230 dB re 1 μ Pa @1 m. The pulse duration is approximately 0.1% to 1% of the two-way travel time from the source to the seafloor. Duty cycle values also range from 0.1% to 1%. Multibeam echosounders transmit pulses in the vertical plane perpendicular to the ship's axis and adjacent sectors to widen the along-track angular aperture. These systems can insonify with across-track apertures up to 150°. Interested readers are referred to Lurton and DeRuiter (2011) and Lurton (2016) for a concise review of this subject. Regarding the potential effects of echosounders on ecosystems, Lurton and DeRuiter (2011) conclude that despite the high power transmitted by these acoustic devices, the short duration of their pulses and their high spatial directivity make these systems unlikely to cause physiological injuries to marine fauna. However, field studies suggest that some marine fauna may respond to echosounder signals even though the operating frequency is above their hearing range (Hastie et al 2014, Cholewiak et al (2017), Quick et al 2017).

Whether marine echosounders constitute an anthropogenic stressor to seagrasses remains, to the author's knowledge, an unexplored issue. This article argues that these popular acoustic systems could have significant bio-effects on seagrass meadows. The high directivity and power levels transmitted by these devices could represent a risk if acoustic beams are radiated in the range of the natural or resonance frequencies of lacunae. In this study, lacunae resonance frequencies are computed for realistic geometries of cross-sections of *Halodule wrightii* and *Syringodium filiforme* leaves. The two species exemplify marine angiosperms with low and high plant-tissue rigidity, respectively (Touchette *et al* 2014). The interaction of the ultrasonic field with the leaf is studied in the framework of linear elastodynamics. The theoretical equations are numerically solved using a finite element approach.

2. Methods

The leaves of *H. wrightii* are thin, flat and tinsel-like and are typically 10–30 cm in length. The larger lacunae are cylindrical in cross-section, with diameters of approximately 100 μ m. These lacunae are symmetrically located with respect to the central axis of the leaf cross-section (figure 1(a)). *H. wrightii* is a marine species with surprisingly elastic tissue. *H. wrightii* elastic modulus, depicting the flexibility of plant tissue, is approximately 1 MPa (Touchette *et al* 2014). The leaf blades of *S. filiforme* are cylindrical in cross-section and are up to 50 cm in length. Their larger lacunae have an approximate elliptical cross-section with major and minor axes of approximately 200 μ m and 125 μ m, respectively (figure 1(b)). Cavities with a major axis aligned with the radial direction surround the centre of the leaf cross-section. The elastic modulus of the *S. filiforme* tissue is approximately 30 MPa and is one of the most rigid tissues among seagrass species (Touchette *et al* 2014).

Theoretically, the geometry of the leaves of *H. wrightii* and *S. filiforme* can be described as a very slender structure oriented along the vertical axis with a length much greater than the cross-section area. Mathematically, the strains associated with the vertical length are assumed to be small compared to the cross-sectional strains, since they are constrained by the nearby material (plain strain). This assumption reduces the analysis of the ultrasound-leaf interaction to a two-dimensional problem within the leaf cross section. Moreover, it is also assumed that leaf tissues are constituted by a linearly elastic, homogeneous and isotropic material. Under these assumptions, the ultrasound-leaf interaction is mathematically described as follows:





1951–1959¹, with the permission of the Acoustical Society of America. Only the lacunae with the largest size are displayed (dashed lines). Horizontal black scale bars are 0.5 mm in length.

$$\rho \frac{\partial^2 u}{\partial t^2} = \nabla . \sigma \tag{1}$$

where ρ is the tissue density, $u(t) = [u_x(x, y, t) u_y(x, y, t)]$ is the displacement vector of material points with respect to time t and σ is the symmetric stress tensor. Equation (1) is completed with the constitutive equation:

$$\sigma = D\varepsilon \tag{2}$$

With

$$D = \begin{bmatrix} \lambda + 2\mu & \lambda & 0 \\ \lambda & \lambda + 2\mu & 0 \\ 0 & 0 & \mu \end{bmatrix}$$
$$\sigma = [\sigma_{xx} \sigma_{yy} \sigma_{xy}]; \sigma_{zz} = \frac{\lambda}{2(\lambda + \mu)}(\sigma_{xx} + \sigma_{yy})$$
$$\varepsilon = [\varepsilon_{xx} \varepsilon_{yy} \varepsilon_{xy}] = \left[\frac{\partial u_x}{\partial x} \frac{\partial u_y}{\partial y} \frac{\partial u_x}{\partial y}\right]$$

where λ and μ are the Lamé parameters. These are derived from the previously reported bulk elastic modulus and a Poisson ratio of 0.3 (Enenstein *et al* 2013). Geometrically, the strain component ε_{ii} (i = x, y) is the relative change in length along the x_i -axis, whereas ε_{xy} is proportional to the change in angle between the initially orthogonal coordinate axes x and y. When strains are small, equation (2) assumes that the relation between the stress and the strain tensors is approximately linear (Hooke's law). The model described by equations (1) and (2) is supplemented by boundary conditions to obtain a unique solution of the deformation field u(x, y, t). A constraint on the normal stress (Neumann boundary condition) is prescribed at the external boundary of the leaf. The boundary condition takes the form $\sigma n = -P(t) \cdot n$, where n is the outward unit normal on the boundary and P(t) is the overall pressure generated by the water column and the ultrasound field. At the lacunae wall, boundary conditions are either $\sigma . n = 0$ (where *n* is the outward unit normal on the internal boundary) when there is no internal pressure or $\left(\sigma + Z_g \frac{\partial u}{\partial t}\right) \cdot n \Big|_{internal} = 0$ when the lacunae is pressurized. In the latter, Z_g is the acoustic impedance for the gas at the internal boundary wall (Bird *et al* 1960).

Leaves of H. wrightii and S. filiforme are assumed to be at a depth of 20 m in the numerical simulations, which is the lower depth limit for both species (Short et al 2010a, b). Thus, the leaf tissue is subjected to a constant compressional load Pw of 300 kPa due to the pressure of the water column. A maximal lacunae pressure PL of approximately 10 kPa was reported for S. isoetifolium and H. ovalis (Brodersen et al 2018). In the absence of data, this value of the maximal lacunae pressure is also assumed for H. wrightii and S. filiforme.



An acoustic pressure load $P_E(t) = P_e.sin(\omega t)$ (where P_e and ω are the amplitude and frequency, respectively) transmitted from a virtual echosounder at the sea surface is added to P_w . The source level of the echosounder is assumed to be 230 dB re 1 μ Pa @1 m, which implies a pressure amplitude P_e of 16 kPa at 20 m depth. Due to linearity, the problem of the leaf-ultrasound interaction equation (1) can be split into the determination of the tissue deformation $u_o(x,y)$ due to the static pressure field P_w :

$$\nabla \sigma_{o} = 0; \ \sigma_{o} \cdot n|_{external} = -P_{w} \cdot n|_{external}; \begin{cases} \sigma_{o} \cdot n|_{internal} = 0\\ or\\ \sigma_{o} \cdot n|_{internal} = -P_{L} \cdot n|_{internal} \end{cases}$$
(3)

The determination of the tissue deformation $u_E(x, y, t)$ due to the acoustic load $P_E(t)$ can be expressed as follows:

$$-\rho\omega^{2}u_{e} = \nabla .\sigma_{e}; \ \sigma_{e}.n|_{external} = -P_{e}.n|_{external}; \begin{cases} \sigma_{e}.n|_{internal} = 0\\ or\\ (\sigma_{e} + i\omega Z_{g}u_{e}).n|_{internal} = 0 \end{cases}$$
(4)

where the time harmonic dependence $u_E(x, y, t) = u_e(x, y).\sin(\omega t)$ and $\sigma_E(x, y, t) = \sigma_e(x, y).\sin(\omega t)$ are considered. The time harmonic dependence is justified by the fact that most echosounders transmit pulses defined by continuous wave (CW) signals (sine waves at a nominal frequency and with a time-limited amplitude). Moreover, pulses are about 20–200 cycles long with duty cycles of the order of a few thousandths (Lurton 2016). Miller (1977) reported for Elodea leaves that pulse exposures with 10 cycles long and duty cycles of 10⁻⁴, already have cell death thresholds near those for CW exposures with the same on-time. For a generic ω , equation (4) defines a continuous eigenvalue problem for the pair (u_e, ω). The eigenvalues correspond to the natural resonance frequencies of the plant cross-section. Strong deformations in the tissue structure are expected when the tissue is insonified with frequencies close to the natural frequencies. Finally, the total deformation field and stress are given by $u(x, y, t) = u_o(x, y) + u_e(x, y).\sin(\omega t)$ and $\sigma(x, y, t) = \sigma_o(x, y) + \sigma_e(x, y).\sin(\omega t)$, respectively.

A standard Galerkin finite element method has been employed to spatially discretize equations (3) and (4). To do so, the leaf geometry is subdivided into a finite number of area elements (triangles). The corners of the elements are called nodes. The discretization of equations (3) and (4) results in an algebraic system of equations for the values of the displacement field at the nodes. Once solved, low-order piecewise polynomials are usually employed to interpolate the solution from the nodes to other locations of the physical domain. The specific mathematical expressions of the procedure are not replicated here, as they can be found in textbooks about finite elements (e.g., Dhatt and Touzot 1984, Zienkiewicz and Taylor 1995).

3. Results

According to the finite element methodology, the domain geometry of the leaf of *H wrightii* was tessellated into 7526 triangular elements with characteristic sizes ranging from 2.5 μ m near the cavity surface to 9.4 μ m at the external boundary (figure 2(a)). Similarly, a mesh with 13 300 triangular elements and resolutions between 6.7 μ m and 19.6 μ m was employed to discretize the leaf of *S filiforme* (figure 2(b)). Computational leaf representations capture the main geometrical aspects of the cross sections displayed in figure 1.

Natural frequencies of oscillations are first computed for each leaf and pressurized condition, considering the corresponding elastic parameters previously mentioned. Only the first ten natural frequencies were computed, since they are the frequencies within the spectral range of interest. For *H. wrightii*, natural oscillation frequencies range between 20 kHz and 200 kHz under unpressurized conditions (figure 3(a)). The results reveal that a significant number of natural vibration frequencies are within or near the frequency bands typical of echosounder operations. A similar situation is found under lacunae pressurization (figure 3(a)).

Natural oscillations of *S. filiforme* occur at higher frequencies than the oscillations in the previous case (figure 3(b)). This results from the rigidity of the biological tissue in this seagrass species. Comparisons of natural frequencies under unpressurized conditions with the spectral operation bands of echosounders show that the former are within or near the range of the latter, except for the three last oscillation modes. Moreover, figure 3(b) shows a substantial overlap between natural vibrations and echosounder frequencies for this seagrass species. A significant number of natural frequencies lie within or near the frequency bands of 200 kHz and 400 kHz, whether the lacunae are pressurized or not. The former is the frequency band in which the navigation echosounders normally operate.

Forces and torques have been computed for leaves at 20 m depth excited with ultrasound transmissions at 200 kHz with a power of 230 dB re 1 μ Pa @1 m. As previously indicated, this setup corresponds to a typical









Figure 3. Natural frequencies under internal unpressurized (triangles) and pressurized (squares) conditions for the (a) *H. wrightii* and (b) *S. filiforme* leave cross-sections. Spectral bands of echosounder operations are displayed in grey.

configuration for echosounder operations in shallow regions. An equivalent tensile (or von Mises) stress σ_M is derived from the resulting forces and torques (Sadd 2014). This magnitude encodes different components of the stress into a scalar tensile stress that generates an equal distortion energy in the material. The equivalent tensile stress facilitates comparison with experimental data.

No significant differences were found between the unpressurized and pressurized cases at the excitation frequency considered here, and for this reason, only results from the former case are shown. Figure 4(a) displays the deformation field resulting from the cross-section of *H. wrightii* at the most stretched stage. Most of the observed deformation results from the compression of the flexible tissue induced by the water column. The highest amplitudes of σ_M are located between lacunae, where the curvature of the distorted lacunae boundary is maximum. Stress amplitudes can exceed 0.7 N mm⁻² at these locations. This value is below the tensile strength, the maximum stress that a material can withstand while being stretched before tearing, as measured for the leaf tissues of other *Halodule* species (4.36 ± 1.36 N mm⁻², De los Santos *et al* 2012).

Similar computations were performed for the leaf cross-section of *S. filiforme* (figure 4(b)). Unlike the case of *H. wrightii*, the rigidity of the leaf tissue prevents the appearance of large deformations under compression. The highest amplitudes of the equivalent tensile stress are located in the inner region determined by the lacunae internal vertices around the leaf geometric centre. Points of high stress amplitudes are also found at the external vertices of the lacunae. The maximum stress amplitude of 0.8 N mm⁻² is in the range of the tensile strength reported for the leaf tissues of other *Syringodium* species (0.69 \pm 0.39 N mm⁻², De los Santos *et al* 2012). Thus, plant-tissue damage could result under these conditions.

The variation in the highest amplitudes of σ_M is not consistent with depth (figure 5). This is due to the different variations with depth of acoustic and water pressure loads. The former varies inversely as the square of the distance to the transmitter, while the latter increases linearly with depth. The acoustic pressure load







dominates the stress at very shallow water depths (a few metres). At higher depths, stresses are mostly determined by the pressure load from the water column. A minimum in the highest amplitude value of $\sigma_{\rm M}$ occurs at the transition between the previously described load regimes. This transition is observed at approximately 10 m depth in the present study (figure 5).

4. Discussion

The potential effects of echosounders on the seagrass population were analysed and quantified in this study. Natural oscillation frequencies of seagrass leaves were obtained based on a mechanistic model, near-real geometries and measured mechanical traits of leaf tissues. Specifically, the theoretical model assumes that leaf tissues are constituted by a linearly elastic, homogeneous and isotropic material. An advantage of this assumption is that its implementation is fully supported by the mechanical parameters reported in the literature (Touchette *et al* 2014). However, seagrasses show a complex leaf blade anatomy and ultrastructure. Seagrass leaves are generally characterised by the existence of cutile, epidermis, fibres, mesophyll tissue and phyllospheres (Kuo and den Hartog 2006). These structures have different compositions and mechanical traits, and their



mechanical response could deviate from the assumed leaf elasticity when mechanical excitations exceed a certain threshold. Additional mechanical characterisations of the leaf tissue (e.g., dissipative and non-linear properties or the criteria for the onset of damage) would result in more accurate tissue models, but in the absence of suitable data, these must be presently ignored.

The model geometry, although realistic, simplifies the real geometry of the plant cross-section up to a certain scale. Specifically, small gas cavities and intercellular channels coexist with larger lacunae in seagrass leaves (Miller 1979, Kuo and den Hartog 2006). According to the size of these cavities, their resonance frequencies are well above (>1 MHz; Miller 1979) the range of frequencies of echosounder operations. Thus, their potential effects are negligible in the framework of this study. A model geometry that only includes those leaf structures that strongly interact with the ultrasound field transmitted by echosounders is a reasonable approximation.

Natural oscillation frequencies of the leaf cross-sections of *H. wrightii* and *S. filiforme* were computed within the previously discussed theoretical framework. *H. wrightii* and *S. filiforme* exemplify seagrass cases with more flexible and rigid leaf tissues, respectively. The size and shape of the lacunae of these species also differ. Despite their differences, computational results show significant overlaps between the natural frequencies and spectral bands of echosounder operations of both species. Overlaps mostly occur at frequency bands lower than 120 kHz for *H. wrightii*. Conversely, overlaps between natural and operating frequencies are concentrated at 200 kHz and 400 kHz for *S. filiforme*.

When the echosounder operates at the leaf natural frequency, all locations of the leaf cross section vibrate at the same frequency, with a constant amplitude pattern and relative phase (natural vibration mode). The energy transfer from the echosounder transmission to the vibration mode is maximum. This resonance mechanism can perturb the tissue structure of the leaf. A plausible scenario was simulated to further investigate this issue. The results suggest two possible scenarios in which acoustic transmissions could result in stresses with a significant impact on tissue integrity. In very shallow conditions, the power levels transmitted by an echosounder at spectral bands near the lacunae natural frequencies induce strong forces and torques in the leaf tissue. At higher depths, the leaf structure is compressed by the dominant pressure of the water column. Despite the decrease in the acoustic pressure due to the distance from the source, this produces a stress field resulting from the pressure at depth, and the tensile strength of the tissue could be exceeded during the stretching phase. Locations of high curvature at the lacunae boundary and inter-lacunae spaces are where perturbations from echosounder transmissions are more prominent. This finding establishes a causal relationship between the stressor and its effect, indicating where to focus to determine the effects of echosounder transmissions in leaves.

Recreational boats are relatively small and powerful crafts that can access shallow and remote coastal areas due to their manoeuvrability and accessibility. Globally, the number of recreational boats has significantly increased with economic growth, and, consequently, their traffic has increased in nearshore areas (Burgin and Hardiman 2011). These nearshore areas are often marine wildlife habitats. As their visiting and anchoring sites are usually far away from other sources of anthropogenic impacts, recreational vessels tend to be a major source of anthropogenic impacts at these sites. For this reason, there has been increasing concern about their interactions with the nearshore marine environment (European Commission DG ENV 2007). A variety of mechanisms, including exhaust and other emissions, propeller contact, turbulence from propulsion systems, waves produced by movement, propeller noise, and anchoring, can mediate these interactions (Murphy and Eaton 1983, Wagner 1994, Mumma *et al* 1996, Abadie *et al* 2016). In turn, each of these mechanisms may have multiple effects on the marine ecosystem, including declines in submerged vegetation (Asplund and Cook 1997). Unfortunately, not all of the mechanisms by which recreational boating interacts with ecosystems have been elucidated. This may limit the effectiveness of environmental management for mitigating the harmful effects related to this anthropogenic activity.

For most recreational boats, an echosounder is considered an essential piece of navigation equipment. These devices are particularly helpful when approaching shallow waters and to support activities like fishing. Thus, nearshore regions of heavy recreational boating could be significantly exposed to echosounder ultrasound radiation. Seagrass meadows are among them. A rough estimate of the spatial scales potentially exposed to the ultrasound radiation can be obtained by considering the density of recreational boat traffic and assuming typical navigation parameters. For example, on the busiest day of the high season, Balaguer *et al* (2011) computed a total of 6082 recreational boats navigating around the Mallorca Island. The latter is the main island in the Balearic archipielago (Spain) where the largest community of Posidonia oceanica in the Mediterranean Sea is located. For an average depth of 20 m, a transmission angular aperture of 5° and transit time of 1 hour at 10 knots (5 m s⁻¹), the total area exposed to echosounder transmissions is about 200 km². In this case, a seagrass leaf would be exposed 0.35 s to ultrasound radiation under the passage of a recreational boat.

The findings of the present study suggest that marine echosounders transmissions could generate harmful effects on exposed seagrass meadows. The identification of this previously unnoticed anthropogenic stressor, results from a theoretical framework limited by the assumptions and idealizations required to make the problem tractable. In this regard, the study is intended to highlight the potential risk to seagrass meadows posed by



marine echosounders and to encourage and guide future experimental and observational assessments on this matter.

ORCID iDs

A Alvarez l https://orcid.org/0000-0001-6583-8515

References

- Abadie A, Lejeune P, Pergent G and Gobert S 2016 From mechanical to chemical impact of anchoring in seagrasses: the premises of anthropogenic patch generation in *Posidonia oceanica* meadows *Mar. Poll. Bull.* **109** 61–71
- Asplund T R and Cook C M 1997 Effects of motor boats on submerged aquatic macrophytes *Lake and Reserv. Manag.* 13 1–12 Balaguer P, Diedrich A, Sarda R, Fuster M, Cañellas B and Tintore J 2011 Spatial analysis of recreational boatong as a first step for marine spatial planning in Mallorca (Balearic Islands, Spain) *Ocean Coast. Manag.* 54 241–9
- Bird J F, Hart R W and McClure F T 1960 Vibrations of thick-walled hollow cylinders: exact numerical solutions J. Acoust. Soc. Am. 32 1404–12
- Brodersen K E, Kühl M, Nielsen D A, Pedersen O and Larkum A W 2018 *Rhizome, Root/Sediment Interactions, Aerenchyma and Internal Pressure Changes in Seagrasses* ed A W Larkum, G A Kendrick and P J Ralph (The Netherlands: Seagrasses of Australia, Springer) pp 393–418
- Burgin S and Hardiman N 2011 The direct physical, chemical and biotic impacts on Australian coastal waters due to recreational boating *Biodivers. Conserv.* 20 683–701
- Cholewiak D, DeAngelis A I, Palka D, Corkeron P J and Van Parijs S M 2017 Beaked whales demonstrate a marked acoustic response to the use of shipboard echosounders *Roy. Soc. Open Sci.* **4** 170940
- De los Santos C B *et al* 2012 Leaf-fracture properties correlated with nutritional traits in nine Australian seagrass species: implications for susceptibility to herbivory *Mar. Ecol. Prog. Ser.* **458** 89–102
- Denninson W C et al 1993 Assessing water quality with submersed aquatic vegetation: habitat requirements as barometers of chesapeake bay health *Bioscience* 43 86–94

Dhatt G and Touzot G 1984 The Finite Element Displayed (New York: Wiley) pp. 526

- Duarte C M 2002 The future of seagrass meadows Environ. Conserv. 29 192-206
- Duarte C M, Middelburg J and Caraco N 2005 Major role of marine vegetation on the oceanic carbon cycle Biogeoscience 2 1-8

Duffy J E 2006 Biodiversity and the functioning of seagrass ecosystems Mar. Ecol. Prog. Ser. 311 233-50

- European Commission DG ENV 2007 Environmental Impacts of Recreational Boating. Science for Environment Policy. European Commission DG Environment News Alert Service 87 (EC: BIO Intelligence Service) p 1 https://ec.europa.eu/environment/integration/research/ newsalert/pdf/87na2_en.pdf
- Enenstein G, Dolder C, Wilson P S and Hermand J-P 2013 Investigation of low-frequency acoustic tissue properties of seagrass *Proc. Meet. Acoust.* **19** 005007
- Fourqurean J W, Duarte C M, Kennedy H, Marba N, Holmer M, Mateo M A, Apostolaki E T, Kendrick G A, Krause-Jensen D and McGlathery K J 2012 Seagrass ecosystems as a globally significant carbon stock Nat. Geosci. 5 505–9
- Grice A M, Loneragan N R and Dennison W C 1996 Light intensity and the interaction between physiology, morphology and stable isotope ratios in five species of seagrass J. Exp. Mar. Biol. Ecol. 195 91–110
- Hastie G D, Donovan C, Götz T and Janik V M 2014 Behavioral responses by grey seals (Halichoerus grypus) to high frequency sonar *Mar. Pollut. Bull.* **79** 205–10
- Heck K L, Jr, Carruthers T J B, Duarte C M, Hughes A R, Kendrick G, Orth R J and Williams S W 2008 Trophic transfers from seagrass meadows subsidize diverse marine and terrestrial consumers *Ecosystems* 11 1198–210
- Komatsu T, Igarashi C, Tatsukawa K, Sultana S, Matsuoka Y and Harada S 2003 Use of multi-beam sonar to map seagrass beds in Otsuchi Bay on the Sanriku Coast of Japan *Aquat. Living Resour.* **16** 223–30
- Kuo J and den Hartog C 2006 Seagrass morphology, anatomy, and ultrastructure Seagrasses: Biology, Ecology and Conservation ed A W D Larkum, R J Orth and C M Duarte (The Netherlands: Springer) pp. 51–87
- Lurton X and DeRuiter S 2011 Sound radiation of seafloor-mapping echosounders in the water column, in relation to the risks posed to marine mammals *Int. Hydrogr. Rev.* **6**7–17
- Lurton X 2016 Modelling of the sound field radiated by multibeam echosounders for acoustical impact assessment *Appl. Acoust.* 101 201–21 Lyons A P L and Abraham D A 1999 Statistical characterization of high frequency shallow-water seafloor backscatter *J. Acoust. Soc. Am.* 106 1307–15
- McCarthy E M and Sabol B 2000 Acoustic characterization of submerged aquatic vegetation: military and environmental monitoring applications Proc. of OCEANS 2000 MTS/IEEE Conf. and Exhibition IEEE 3 (Piscataway, NJ) 1957–61
- McGlathery K J, Sundback K and Anderson I C 2007 Eutrophication in shallow coastal bays and lagoons: the role of plants in the coastal filter Mar. Ecol. Prog. Ser. 348 1–18
- Miller D L 1977 The effects of ultrasonic activation of gas bodies in Elodea leaves during continuous and pulsed irradiation at 1 MHz *Ultrasound Med. Biol.* **3** 221–40
- Miller D L 1979 Cell death thresholds in Elodea for 0.45-10 MHz ultrasound compared to gas-body resonance theory Ultrasound Med. Biol. 5 351–7

Miller D L 1984 Gas body activation Ultrasonics 22 261-9

Miller D L and Thomas R D 1993 Ultrasonic gas body activation in Elodea leaves and the mechanical index *Ultrasound Med. Biol.* **19** 343–51 Mumma M T, Cichra C E and Sowards J T 1996 Effects of recreation on the submersed aquatic plant community of Rainbow River, Florida *J. Aquat. Plant Manage* **34** 53–6 http://www.apms.org/1996/12/journal-of-aquatic-plant-management-volume-34-1996/

Murphy K J and Eaton J W 1983 Effects of pleasure-boat traffic on macrophyte growth in canals *J. Appl. Ecol.* **20** 713–29 Orth R J *et al* 2006 A global crisis for seagrass ecosystems *Bioscience* **56** 986–7

Quick N, Scott-Hayward L, Sadykova D, Nowacek D and Read A 2017 Effects of a scientific echo sounder on the behavior of short-finned pilot whales (Globicephala macrorhynchus) *Can. J. Fish. Aquat. Sci.* 74 716–26

Sadd MH 2014 Elasticity: Theory, Applications and Numerics. (Burlington, MA: Academic) pp. 600



- Short F T, Carruthers T J R, van Tussenbroek B and Zieman J 2010a Halodule wrightii. the IUCN red list of threatened species **2010** e. T173372A7001725
- Short F T, Carruthers T J R, van Tussenbroek B and Zieman J 2010b Syringodium filiforme. the IUCN red list of threatened species **2010** e. T173378A7003203
- Touchette B W, Marcus S E and Adams E C 2014 Bulk elastic moduli and solute potentials in leaves of freshwater, coastal and marine hydrophytes Are marine plants more rigid? AOB Plants 6

Wagner K J 1994 Of hammocks and horsepower: the noise issue at lakes Lakeline 14 24-8

 Waycott M *et al* 2009 Accelerating loss of seagrasses across the globe threatens coastal ecosystems *Proc. Natl Acad. Sci. USA* 106 12377–81
Wilson P S and Dunton K H 2009 Laboratory investigation of the acoustic response of seagrass tissue in the frequency band 0.5-2.5 kHz *J. Acoust. Soc. Am.* 125 1951–9

- Zienkiewicz O C and Taylor R L 1995 The finite element method *Basic Formulation and Linear Problems* (Maidenhead: McGraw-Hill) pp. 648
- Zarnoch C B, Hoellein T J, Furman B T and Peterson B J 2017 Eelgrass meadows, Zostera marina (L.), facilitate the ecosystem service of nitrogen removal during stimulated nutrient pulses in Shinnecock Bay Mar. Poll. Bull. 124 376–87